

特点characteristic

- 1、体积小, 100/120A触点切换能力
Small size,60/80A switching capability.
- 2、线圈功耗小、温升极低
Low coil consumption, ultra-low temperature rise
- 3、触点接触电阻小, 电接触稳定性好
Low contact resistance
- 4、抗冲击、抗振动能能力强
Strong anti-shock and anti-vibration capability 5、

外形尺寸: (52×43×22) mm

Outline size: (52×43×22) mm

**触点参数Contact parameters**

型号Model	WL09E
触点形式Contact form	1A、1B
最大切换电流Maximum switching current	100A/120A
最大切换电压Maximum switching voltage	250AC
最大切换功率Maximum switching power	25000VA/30000VA
触点负载 (阻性) Contact load (resistive)	100A 250VAC 120A 250VAC

性能参数performance parameter

触点材料Contact material	银合金 Ag alloy	
接触电阻Contact resistance	100A: Max;1.0mΩ	120A: Max;0.8mΩ
动作时间Action time	≤20S	
释放时间Release time	≤20S	
绝缘电阻Insulation resistance	Min 1000MΩ (500VDC)	
介质耐压 Dielectric Strength	断开触点间 Between Open contacts	AC 2000VAC 50/60Hz 1min
	触点线圈间 Between contact coils	AC 4000VAC 50/60Hz 1min
冲击 to attack	稳定性stability	100m/S ² (10g)
	强度strength	1000m/S ² (100g)
振动Vibration	10~55Hz 双振幅 Double Amplitude 1.5mm	
机械寿命Mechanical endurance min	5×10 ⁵	
电气寿命Electrial edurance min	1×10 ⁴	
相对湿度Humidity	98%RH,40°C	
环境温度Ambient temperature	-40~+70°C	
重量Weight	约Approx 80g	

订货示例Ordering example

	WL09E	-F	-1	12	D	B	X
继电器型号 Type							
密封型式: F-防尘式 Construction: F-Flux proofed							
继电器触点组数: 1-1组触点 Number of Poles: 1-1 group							
线圈电压: 9, 12, 24, 48VDC Coil Voltage: 9, 12, 24, 48VDC							
线圈形式: 无-单线圈, D-双线圈 Coil type: Nil-Single coil, D-Double coil							
触点形式: B-常闭, M-常开 Contact Arrangement: B-N/C, M-N/O							
特规参数: 根据客户要求定制 无-标准型 Special parameters: customized according to customer requirements Nil-standard							

线圈Coil

线圈功耗Coil power	单线圈: 2.3W, 双线圈: 4.6W Single Coil: 2.3W, Double Coil: 4.6W
----------------	--

线圈参数Coil parameters (at 20°C)

线圈形式 Coil type	额定电压 rated Voltage	线圈电阻 Coil Resistance	动作电压 Pick-up Voltage 额定电压的75% 75% of rated voltage	脉冲宽度 Pulse Duration	功率 Coil Power
	VDC	$\Omega \pm 10\%$	VDC	ms	W
单线圈 Single coil	9	35	6.75	100	2.3
	12	63	9	100	
	24	250	18	100	
	48	1002	36	100	
双线圈 Double coil	9	2×17.5	6.75	100	4.6
	12	2×31.5	9	100	
	24	2×125	18	100	
	48	2×501	36	100	

外形及安装图 Outline and installation drawing

Outline Dimensions
外形图

